Antifreeze

Lube Oils



Options

- 1.5" x 10' suction and discharge hoses
- Total Control Systems "Weights & Measures" meter / register with optional:
- Strainer / air eliminator
- Preset batch control
- Ticket printer
- Filter housing and cartridges
- Quick Couplers, discharge nozzles, suction wands
- Suction strainer to protect pump
- 50' electrical cord
- · Explosion Proof motor and or electrical enclosure
- Solid Rubber tires
- · Grounding cable
- · Can be used with fuels and general chemical transfer (contact Semler for compatibility and electrical requirements)

Don't see an option that meets your needs? Just ask, the options and configurations available are endless...

Semler Industries Inc.

3800 North Carnation Street Franklin Park, IL 60131 USA Phone: (847) 671-5650 Fax: (847) 671-7686 info@semlerindustries.com

www.semlerindustries.com



Model OTC-25/12-S-10/10- T-T- MAT- # -S-X-R front view shown.

Anti-Freeze & Lube Oil **Transfer Carts**





Model ATC-35S-S-10/10-T-T- # - # -S-S-P rear view shown

LUBE OIL & ANTI-FREEZE TRANSFER CART INCLUDES

- Blackmen variable speed pump with two pre-set flow rates (6 - 35 GPM flow range)
- Compatible with antifreeze, oils, common solvents, and chemicals that are compatible with mild steel (Clean products only)
- Unique frame design to collect drips from spout, protect equipment, and allow for easy hose storage
- Blackmer self-priming, ductile-iron, rotary sliding-vane pump with internal pressure relief


- Pneumatic tires
- 120 Volt, single-phase, 15 Amp power requirement for multi-speed unit or 20 Amp power requirement for single speed unit
- TEFC motor
- 25' power cord with 3-prong plug
- Weather-tight (NEMA 4) Electrical enclosure
- All electrical components over 18" high to assist in safe operation and compliance with NFPA30A

Names & logos may be trademarks of their respective owners and are used under license or permission herein.



Ordering Code Example: 0TC-25/12-S-10/10-T-N-MP-#-S-S-R

Oil transfer cart with 2 preset speeds, 25 GPM or 12 GPM, (for different viscosity oils), strainer, 10' hose in and out, TEFC motor and enclosure, Meter with preset, no grounding cable, suction wand, discharge spout with valve, solid rubber tires.



Semler Industries is proud to offer the most durable, rugged, and reliable portable pumping system on the market. With built-in nozzle holsters and drip tanks, metal framework protecting pump & motor, and a portfolio of options, this unit eliminates all the common problems encountered when using other portable pumping carts on the market.

Semler's Complete Line of Engine Fluid Transfer Equipment



Oil and Lubricant Transfer Systems



Fuel Polishing



Antifreeze and Engine Fluid Transfer Systems



High Flow Diesel Transfer Systems



Diesel Exhaust Fluid Transfer Systems



FT-25 Portable Fuel Transfer



Semler Industries Inc.

3800 North Carnation Street Franklin Park, IL 60131 USA Phone: (847) 671-5650 Fax: (847) 671-7686 info@semlerindustries.com

www.semlerindustries.com